

Discover the Proforge Folding Rolls Collection



- Top Quality Range
- Hydraulic Folding
- Widths from 4.3m to 12.3m
- Rings – 20" and 24"
- Plain and Breaker options
- Standard or Heavy Duty Options
- 3 or 5 Section
- Optional Extras on all Models



Through extensive design and testing from roller experts, we are pleased to present a high quality built range of hydraulic folding rolls designed for long life with minimum maintenance.

UK MANUFACTURED 

PROFORGE[®]

Folding Roll - Standard (3 sections)



Folding Roll - Standard 3 Section Features

- 1 Fully hydraulic horizontal folding and unfolding
- 2 60mm axles with high quality grease-able bearings
- 3 4 spoke rings for strength and weight.
- 4 Wings supported in cradles for transport, reducing axle and bearing fatigue
- 5 Floating wings to follow contours of the ground
- 6 10ply tyres
- 7 2.4m transport width

Optional Extras

- 1 Wheel eradicator tines
- 2 Stone Trays
- 3 Centre pivoting wings

Technical Information

Working Width (m)	Ring	Weight 20" (kg)	Weight 24" (kg)
4.3	Plain	1900	2595
4.3	Plain & Breaker	2239	2950
5.3	Plain	2598	3000
5.3	Plain & Breaker	2954	3340
6.3	Plain	2750	3380
6.3	Plain & Breaker	3380	N/A

Folding Roll - Heavy Duty (3 sections)



Folding Roll - Heavy Duty 3 Section Features

- 1 Heavy duty construction and frame design
- 2 Fully hydraulic folding and unfolding
- 3 60mm axles with high quality grease-able bearings
- 4 4 spoke rings for strength and weight
- 5 Wings supported in cradles for transport, reducing axle and bearing fatigue
- 6 Floating wings to follow contours of the ground
- 7 14 ply tyres
- 8 2.5m transport width



Optional Extras

- 1 Hydraulic paddles/shatterboards
- 2 Wheel eradicator tines
- 3 Stone trays
- 4 Centre pivoting wings

Technical Information

Working Width (m)	Ring	Weight 20" (kg)	Weight 24" (kg)
6.3	Plain	2950	3560
6.3	Plain & Breaker	3560	4380
7.3	Plain	3315	4010
7.3	Plain & Breaker	4020	4900
8.3	Plain	3780	5000
8.3	Plain & Breaker	4580	5640

Folding Roll - Standard (5 sections)

Folding Roll - Standard 5 Section Features

- 1 Fully hydraulic horizontal folding and unfolding
- 2 60mm high tensile axles with high quality grease-able triple seal bearings
- 3 4 spoke rings for strength and weight.
- 4 Centre support bearing on all shafts on 12m models
- 5 Centre pivoting wings to follow contours of the ground
- 6 3m transport width
- 7 18ply tyres



Technical Information

Working Width (m)	Ring	Weight 20" (kg)	Weight 24" (kg)
9.3	Plain	4800	6100
9.3	Plain & Breaker	6000	7600
10.3	Plain	5300	6700
10.3	Plain & Breaker	6600	8400
12.3	Plain	6300	8000
12.3	Plain & Breaker	8000	10000

"designed for long life with minimum maintenance"



Distributed by:



PROFORGE GLOBAL www.proforge.co.uk

Distributed by Agri-linc

Randalls Farm, Edenham, Bourne, Lincs. PE10 0LN UK

+44 (0) 1778 591225 machinery@agri-linc.com www.agri-linc.com

Disclaimer

This literature is designed for worldwide circulation. Due to a continuing policy of product improvement, we reserve the right to alter specifications and engineering developments without notice. As machines and parts are exported to many different countries; general information, images and descriptions are provided as a representation so machinery may include optional equipment that is not part of the standard specification. Please consult your local dealer or distributor for further information.

Copyright ©2014. All rights reserved. Agri-Linc® & Proforge® logos are exclusive brands of G. Whyles & Sons. No part of this brochure may be reproduced or transmitted in any form or by any means including photocopying without prior permission in writing from the partners of G. Whyles & Sons trading as Agri-Linc®. E&OE.